


RY-850B 4色

宽幅柔版印刷机
Flexographic Printing Machine

高效 快速 稳定
Flexographic Printing Machine

- 1 液压自动上料
Automatic hydraulic lifting device
- 2 自动光眼纠偏
Automatic optical eye correction
- 3 电晕装置
Corona treatment device
- 4 印刷组
Printing group
- 5 控制台
Control panel



产品特点 Product features

1. 采用陶瓷网纹辊传墨, 停机时自动脱离印刷组。
2. 每组单独的360°周向对版装置及独立的烘干系统。
3. 放料采用磁粉制动(自动恒张力控制)。
4. 收料采用变频电机(自动恒张力控制)。
5. 本机采用进口变频无级调速。
6. 收、放料设计有自动液压升降。
7. 本机功能齐全, 从上料、电晕、纠偏、印刷、收料一次完成。

1. Adopt the anilox roller to spread ink.
2. Unwinding and rewinding are controlled by magnetic power brake, clutch, (or by automatic tension controller of mitsubishi, made in japan)
3. Each printing unit adopt 360° for registration.
4. Each printing unit have one IR drier.
5. The rubber roller can break away automatically while parking, and running at a low speed, in order to avoid ink being dry.
6. The main motor is adopted the import stepless, regulation of frequency conversion.
7. Unwinding, web guiding, printing, IR drying, die cutting, waste, rewinding, strimming, rewinding, can be finished in one process This is an ideal machine for printing factory to print many kinds of paper cup.

主要技术参数 Main Technical Parameters

印刷速度	Printing speed	50m-60m/min
印刷色数	Printing chromatic number	4 colors
进料宽度	Feed width	860mm
最大放卷直径	Max. unwinding diameter	1300mm
最大收卷直径	Max. winding diameter	1300mm
最大印刷尺寸	Max. print size	180-380mm
套印精度	Overprint precision	±0.15mm
电压	Voltage	380V±10%
总功率	Total power	36kw
总气压	Total pressure	0.6MP
重量	Weight	4500kg
外形尺寸	Outline dimension	4500×1800×2250mm

可根据客户要求定制不同规格 / According to customer requirements customize different specifications.

